

**Overview**

- Universal transmitter with HART® communication
- Programmable through integrated USB port or HART® modem
- Sensor calibration for either offset, slope or polynomial adjustment
- Accuracy better than 0.1°C for RTD elements
- Automatic cable compensation calibration (2-wire)
- Fast sampling time < 50 ms
- Galvanic isolated
- ATEX and IECEx certified



**Technical data**

**Ambient conditions**

Operating temperature range	-40 ... 85 °C
Storage temperature range	-50 ... 85 °C
Degree of protection (EN 60529)	IP 55
Humidity	< 98 % RH , condensing
Insulation voltage	1.5 kV AC

**Input signal**

Range	Refer to section "Operating conditions"
Connection variants	2-wire 3-wire 4-wire
Measuring unit	°C °F K
Min. measuring span	10 °C
Resolution	17 bit
RTD measuring current	0.16 mA , continuous
Sample time	≤ 0.1 s
Accuracy	Refer to section "Operating conditions"
CJC-compensation	< 0.5 °C , internal < 0.2 °C , external
Input resistance	> 20 MΩ , typ.
Cable resistance	< 30 Ω/wire , 2-wire < 30 Ω/wire , 3/4-wire (T < 700°C) < 15 Ω/wire , 3/4-wire (T > 700°C)
Repeatability	Refer to section "Operating conditions"
Offset adjustment	± 500 °C , max.
Suppression	50 Hz 60 Hz
Protection	± 35 V DC
Error detection delay	< 2.0 s

**Output signal**

Characteristic	Linear or customised with max. 30 points
Output signal	4 ... 20 mA , 2-wire 20 ... 4 mA , 2-wire
Accuracy	< 0.025 % FSR
Step response time	< 450 ms
Temperature drift	± 0.01 %/K , max.
Load resistance	Rs ≤ (V DC - 7 V)/0.023 A
Resolution	14 bit
Up/Down scaling limits	23 mA / 3.5 mA
Ripple immunity	< 1 % , FSR (1 Vrms, 50Hz...1kHz)
Effect of variations in supply voltage	0.001 %/V
Damping	0 ... 60

**HART® interface**

Properties	Read serial number Read/Change user ID Read/Change configuration Read input signal value Read output signal value Input signal logging 2-point sensor-trim For more information please see 'HART Field Device Specification'
Protocol	HCF standard, Rev.7 including „Temperature Device Family“ commands

**Housing**

Style	Compact transmitter, Ø44 mm DIN form B compatible
Overall size	Refer to section "Dimensional drawings"
Material	Polycarbonate

# 2222

In-head transmitter for CombiTemp- or OEM applications

2222-000#.#

## Technical data

### Power supply

Voltage supply range	7 ... 40 V DC , without DFON touch screen 13.5 ... 40 V DC , with DFON touch screen
Power-up time	< 3 s , RTD, Ohm, mV < 5 s , T/C
Reverse polarity protection	Yes

### Factory settings

Sensor type class	RTD
Sensor type	Pt100
Connection	2-wire
Unit	°C
Output range	0 ... 100 °C
Damping	0 s
Output at sensor fault	23 mA

### IECEX/ATEX II 1G Ex ia IIC T6...T4 Ga

Maximum values for barrier selection, Ui	30 V DC
Maximum values for barrier selection, Ii	95 mA
Maximum values for barrier selection, Pi	750 mW
Internal capacitance, Ci	11 nF 26 nF , with DFON touch screen (ATEX only)
Internal inductance, Li	24 µH 34 µH , with DFON touch screen (ATEX only)
Temperature class, T1 ... T6	- 40 < Tamb < 56 °C
Temperature class, T1 ... T5	- 40 < Tamb < 71 °C - 20 < Tamb < 60 °C, with DFON touch screen (ATEX only)
Temperature class, T1 ... T4	- 40 < Tamb < 80 °C - 20 < Tamb < 60 °C, with DFON touch screen (ATEX only)

### IECEX/ATEX II 1G Ex ia IIC T6...T4 Ga

Sensor circuit, Uo	10.5 V DC
Sensor circuit, Io	19 mA
Sensor circuit, Po	55 mW
Sensor circuit, Co	2 µF
Sensor circuit, Lo	94 mH

### IECEX/ATEX II 3G Ex nA IIC T6...T5 Gc

Voltage supply range, Un	30 V DC , max.
Current rating, In	20 mA
Temperature class, T1 ... T6	- 40 < Tamb < 31 °C
Temperature class, T1 ... T5	- 40 < Tamb < 80 °C
Sensor circuit, Uo	2.3 V DC
Sensor circuit, Io	0.2 mA

### IECEX/ATEX II 3G Ex ec IIC T6...T5 Gc

Voltage supply range, Un	30 V DC , max.
Current rating, In	20 mA
Temperature class, T1 ... T6	- 40 < Tamb < 31 °C
Temperature class, T1 ... T5	- 40 < Tamb < 80 °C
Sensor circuit, Uo	2.3 V DC
Sensor circuit, Io	0.2 mA

### Compliance and approvals


EMC	EN 61326-1 DNV GL - Class A EN 50121-3-2:2016
Namur	NE21
Explosion protection	ATEX II 1G Ex ia IIC T6...T4 Ga ATEX II 3G Ex nA IIC T6...T5 Gc ATEX II 3G Ex ec IIC T6...T5 Gc IECEX Ex ia IIC T6...T4 Ga IECEX Ex nA IIC T6...T5 Gc IECEX Ex ec IIC T6...T5 Gc

**Operating conditions**


Type	Standard	Measuring range	Min. measuring span	Type	Range	Repeatability	Input accuracy	Input temperature drift (by ambient)
Pt25...Pt1000	DIN/EN/IEC 60751	-200...850°C	10°C	Pt100-Pt200	-200...200°C	≤ ± 0.03°C	≤ ± 0.05°C	≤ ± 0.01 °C/°C change
					200...850°C		≤ ± 0.06°C	≤ ± 0.015 °C/°C change
				Pt500	-200...200°C	≤ ± 0.07°C	≤ ± 0.14°C	≤ ± 0.04 °C/°C change
Pt25...Pt1000	a= 0.003902	-150...650°C	10°C	Pt100-Pt200	-150...650°C	≤ ± 0.03°C	≤ ± 0.05°C	≤ ± 0.013 °C/°C change
					200...650°C		≤ ± 0.07°C	≤ ± 0.14°C
				Pt500	-150...200°C	≤ ± 0.08°C	≤ ± 0.16°C	≤ ± 0.044 °C/°C change
Pt25...Pt1000	a= 0.003916	-200...720°C	10°C	Pt100-Pt200	-200...200°C	≤ ± 0.03°C	≤ ± 0.04°C	≤ ± 0.01 °C/°C change
					200...720°C		≤ ± 0.05°C	≤ ± 0.013 °C/°C change
				Pt500	-200...200°C	≤ ± 0.07°C	≤ ± 0.14°C	≤ ± 0.04 °C/°C change
Pt25...Pt1000	a= 0.003920	-200...660°C	10°C	Pt100-Pt200	-200...200°C	≤ ± 0.03°C	≤ ± 0.05°C	≤ ± 0.01 °C/°C change
					200...660°C		≤ ± 0.06°C	≤ ± 0.013 °C/°C change
				Pt500	-200...200°C	≤ ± 0.07°C	≤ ± 0.14°C	≤ ± 0.04 °C/°C change
Ni25...Ni1000	DIN 43760	-60...250°C	10°C	Ni100-Ni200	-60...100°C	≤ ± 0.03°C	≤ ± 0.05°C	≤ ± 0.01 °C/°C change
					100...250°C		≤ ± 0.04°C	≤ ± 0.006 °C/°C change
				Ni500	-60...100°C	≤ ± 0.06°C	≤ ± 0.11°C	≤ ± 0.03 °C/°C change
Cu25...Cu1000	0.428 Ohm/°C	-50...200°C	10°C	Ni1000	-60...100°C	≤ ± 0.03°C	≤ ± 0.06°C	≤ ± 0.015 °C/°C change
					100...250°C	≤ ± 0.02°C	≤ ± 0.04°C	≤ ± 0.01 °C/°C change
				Cu50	-50...200°C	≤ ± 0.04°C	≤ ± 0.08°C	≤ ± 0.02 °C/°C change
B(PtRh30-Pt)	IEC 584	100...1820°C	200°C	Cu100-Cu200	-50...200°C	≤ ± 0.02°C	≤ ± 0.04°C	≤ ± 0.01 °C/°C change
					100...500°C	≤ ± 5°C	≤ ± 10°C	≤ ± 3.3 °C/°C change
					500...1000°C	≤ ± 1°C	≤ ± 2.0°C	≤ ± 0.6 °C/°C change
E(NiCr-CuNi)	IEC 584	-250...1000°C	50°C		1000...1820°C	≤ ± 0.6°C	≤ ± 1.1°C	≤ ± 0.33 °C/°C change
					-250...-40°C	≤ ± 0.5°C	≤ ± 1.03°C	≤ ± 0.3 °C/°C change
					-40...150°C	≤ ± 0.1°C	≤ ± 0.19°C	≤ ± 0.06 °C/°C change
J(Fe-CuNi)	IEC 584	-210...1200°C	50°C		150...1000°C	≤ ± 0.07°C	≤ ± 0.14°C	≤ ± 0.042 °C/°C change
					-210...-40°C	≤ ± 0.25°C	≤ ± 0.52°C	≤ ± 0.16 °C/°C change
					-40...150°C	≤ ± 0.1°C	≤ ± 0.21°C	≤ ± 0.07 °C/°C change
K(NiCr-Ni)	IEC 584	-250...1370°C	100°C		150...1200°C	≤ ± 0.09°C	≤ ± 0.18°C	≤ ± 0.055 °C/°C change
					-250...-40°C	≤ ± 1°C	≤ ± 2.04°C	≤ ± 0.6 °C/°C change
					-40...150°C	≤ ± 0.15°C	≤ ± 0.27°C	≤ ± 0.08 °C/°C change
L(Fe-CuNi)	DIN 43710	-200...900°C	50°C		150...1370°C	≤ ± 0.13°C	≤ ± 0.25°C	≤ ± 0.075 °C/°C change
					-200...50°C	≤ ± 0.17°C	≤ ± 0.33°C	≤ ± 0.1 °C/°C change
					50...620°C	≤ ± 0.1°C	≤ ± 0.20°C	≤ ± 0.06 °C/°C change
N(NiCrSi-NiSi)	IEC 584	-250...1300°C	50°C		620...900°C	≤ ± 0.09°C	≤ ± 0.17°C	≤ ± 0.05 °C/°C change
					-250...-40°C	≤ ± 1.75°C	≤ ± 3.45°C	≤ ± 1.0 °C/°C change
					-40...500°C	≤ ± 0.2°C	≤ ± 0.40°C	≤ ± 0.12 °C/°C change
R(PtRh13-Pt)	IEC 584	-50...1750°C	100°C		500...1300°C	≤ ± 0.13°C	≤ ± 0.26°C	≤ ± 0.08 °C/°C change
					-50...100°C	≤ ± 1.35°C	≤ ± 2.7°C	≤ ± 0.8 °C/°C change
					100...500°C	≤ ± 0.7°C	≤ ± 1.33°C	≤ ± 0.4 °C/°C change
S(PtRh10-Pt)	IEC 584	-50...1760°C	100°C		500...1750°C	≤ ± 0.45°C	≤ ± 0.9°C	≤ ± 0.28 °C/°C change
					-50...100°C	≤ ± 1.3°C	≤ ± 2.5°C	≤ ± 0.75 °C/°C change
					100...500°C	≤ ± 0.7°C	≤ ± 1.37°C	≤ ± 0.41 °C/°C change
T(Cu-CuNi)	IEC 584	-250...400°C	50°C		500...1760°C	≤ ± 0.5°C	≤ ± 1.01°C	≤ ± 0.3 °C/°C change
					-250...-40°C	≤ ± 0.8°C	≤ ± 1.6°C	≤ ± 0.5 °C/°C change
					-40...100°C	≤ ± 0.15°C	≤ ± 0.29°C	≤ ± 0.09 °C/°C change
U(Cu-CuNi)	DIN 43710	-200...600°C	50°C		100...400°C	≤ ± 0.1°C	≤ ± 0.21°C	≤ ± 0.065 °C/°C change
					-200...50°C	≤ ± 0.25°C	≤ ± 0.5°C	≤ ± 0.15 °C/°C change
					50...300°C	≤ ± 0.13°C	≤ ± 0.25°C	≤ ± 0.08 °C/°C change
W5-Re (Type C)	ASTM 988	0...2310°C	100°C		300...600°C	≤ ± 0.09°C	≤ ± 0.17°C	≤ ± 0.05 °C/°C change
					0...1750°C	≤ ± 0.4°C	≤ ± 0.75°C	≤ ± 0.22 °C/°C change
W3-Re (Type D)	ASTM 988	0...2300°C	100°C		1750...2310°C	≤ ± 0.55°C	≤ ± 1.09°C	≤ ± 0.3 °C/°C change
					0...400°C	≤ ± 0.5°C	≤ ± 1°C	≤ ± 0.3 °C/°C change
Linear voltage			5 mV		-140...140 mV	≤ ± 0.005 mV	≤ ± 10 µV	≤ ± 0.007 mV/°C change
Linear voltage			75 mV		-500...2000 mV	≤ ± 0.1 mV	≤ ± 125 µV	≤ ± 0.04 mV/°C change
Linear resistance			5 Ω		0...390 Ω	≤ ± 0.007 Ω	≤ ± 15 mΩ	≤ ± 0.004 Ω/°C change
Linear resistance			5 Ω		0...820 Ω	≤ ± 0.015 Ω	≤ ± 30 mΩ	≤ ± 0.007 Ω/°C change
Linear resistance			50 Ω		0...7000 Ω	≤ ± 0.15 Ω	≤ ± 250 mΩ	≤ ± 0.07 Ω/°C change

**Dimensional drawings (mm)**

**Housing**




Front view




Side view

**Electrical connection**


**RTD**



No cable compensation




3-wire cable compensation




4-wire cable compensation


**T/C**



Internal CJC-compensation




External CJC-compensation, no cable compensation




External CJC-compensation, 3-wire cable compensation

**Electrical connection**


**Potentiometer**



No compensation




3-wire compensation for transfer resistance




4-wire compensation for transfer resistance


**Resistance**



No compensation




3-wire cable compensation




4-wire cable compensation

**Voltage measurement**



**Current measurement**



**Ordering information**

Ordering key - Configuration possibilities see website

	22	22	-	####	.	#
<b>Product</b>	22					
<b>Type</b>						
Universal input / 4-20 mA + HART out / USB		22				
<b>Safety</b>						
Standard						0001
IECEX / ATEX ia						0002
IECEX / ATEX nA						0003
IECEX / ATEX ec						0004
<b>Configuration</b>						
None						0
Programmed acc. to customer specification						C