

LXC-40M

Camera Link®, 4 Megapixel, Monochrome

Article number: 11148640

Overview

- 2048 × 2048 px
- ams (CMOSIS) CMV4000 V3
- 1" CMOS
- 180 fps
- Camera Link® Full
- available



GEN*i*CAM



Technical data

Sensor information

Sensor	ams (CMOSIS) CMV4000 V3
Resolution	2048 × 2048 px
Exposure time	0,03 ... 1000 ms
Pixel size	5.5 × 5.5 µm
Shutter type	Global shutter
Sensor type	1" CMOS

Acquisition formats

Image formats, interface frame rate max.	Full Frame, 2048 × 2048 px, max. 180 fps Binning 2×2, 1024 × 1024 px, max. 180 fps Binning 1×2, 1024 × 2048 px, max. 180 fps Binning 2×1, 2048 × 1024 px, max. 180 fps
Pixel formats	Mono8 Mono10

Image preprocessing

Analog controls	Gain (0 ... 12 dB) Offset (0 ... 63 LSB 10 Bit)
Color models	Mono
Color processing	NA

Camera features

Synchronization	free running trigger
Trigger sources	Hardware Software
Trigger delay	0 ... 2 sec, tracking and buffering of up to 512 trigger signals

Camera features

Sequencer	Automated control for series of images using different sets of parameters
Sequencer parameter	Exposure time gain factor Output ROI Offset x ROI Offset y
Digital inputs	1 input line
Digital outputs	1 output line
Internal image buffer	256 MB

Interfaces and connectors

Data interface	Camera Link Full, connector: 2 x Standard SDR26 (Mini CL)
Process interface	M8 / 8 pins
Power supply	via M8 / 8 pins

Mechanical data

Lens mount	C-mount
Width	60 mm
Height	60 mm
Depth	43,05 mm
Weight	≤ 285 g
Material	housing: aluminum

Electrical data

Voltage supply range +Vs	12 ... 24 V DC (external power supply) 0 ... 12 V (PoCL)
Power consumption	approx. 3,8 W @ 24 VDC approx. 3,8 W @ 12 VDC (PoCL)

LXC-40M

Camera Link®, 4 Megapixel, Monochrome

Article number: 11148640

Technical data

Non-volatile memory

Flash memory size 128 kB

Environmental conditions

Operating temperature +5 ... +64 °C @ T = measurement point

Humidity 10 ... 90 % (non-condensing)

Environmental conditions

Protection class IP 40

Conformity

Conformity CE
RoHS
EAC

Dimension drawing

