



**GIG** VISION **GEN<i>i>CAM**



#### sensor information

sensor	Sony IMX304
resolution	4096 × 3000 px
exposure time	0,001 ... 60000 ms
pixel size	3.45 × 3.45 µm
shutter type	Global shutter
sensor type	1.1" CMOS

#### acquisition formats

image formats, interface	Full Frame, 4096 × 3000 px, max. 10 fps
frame rate max.	Binning 2×2, 2048 × 1500 px, max. 15 fps Binning 2×1, 2048 × 3000 px, max. 15 fps Binning 1×2, 4096 × 1500 px, max. 15 fps
image formats, acquisition	Full Frame, 4096 × 3000 px, max. 15 fps
frame rate max. (Burst Mode)	
pixel formats	Mono8 Mono10

#### image preprocessing

analog controls	Gain (0 ... 48 dB) Offset (0 ... 255 LSB 12 Bit)
color models	Mono

#### interfaces and connectors

data interface	Gigabit Ethernet, Transfer rate 1000 Mb/s/sec, Fast Ethernet, Transfer Rate 100 Mb/s/sec, Connector: 8P8C Modular Jack (RJ45), screwable type
process interface	M8 / 8 pins (SACC-DSI-M8MS-8CON-M8-L180)
power supply	M8 / 8 pins or PoE

#### mechanical data

lens mount	C-mount
width	29 mm
height	29 mm
depth	49 mm

#### mechanical data

weight	≤ 120 g
material	zinc die casting, nickel-plated, IP 40

#### electrical data

voltage supply	12 ... 24 V DC (external power supply)
range +Vs	36 ... 57 V DC (Power over Ethernet)
power consumption	approx. 3,1 W @ 12 VDC and 10 fps approx. 3,5 W @ 48 VDC (PoE) and 10,0 fps

#### non-volatile memory

flash memory size	128 kB
-------------------	--------

#### environmental conditions

operating temperature	+5 ... +65 °C @ T = measurement point
humidity	10 ... 90 % (non-condensing)
protection class	IP 40

#### digital I/Os

lines	1 input line 1 output line 2 general purpose lines
-------	--

#### conformity

conformity	CE RoHS KC (MISP-REI-BkR-VCXG-124M) EAC
------------	--

# VCXG-124M

Gigabit Ethernet, 12,3 Megapixel, Monochrome

Article number: 11172630

## dimension drawing

