

## EAL580-SV - EtherCAT

Solid shaft with synchro flange

Optical multturn encoders 18 bit ST / 16 bit MT, EtherCAT

### Overview

- Absolute encoder multturn
- Optical sensing method
- Max. resolution: singleturn 18 bit, multturn 16 bit
- Synchro flange
- LED status display
- EtherCAT
- Maximum resistant against magnetic fields



### Technical data

#### Technical data - electrical ratings

Voltage supply	10...30 VDC
Reverse polarity protection	Yes
Consumption w/o load	≤100 mA (24 VDC)
Interface	EtherCAT
Function	Multiturn
Steps per revolution	≤262144 / 18 bit (adjustable)
Number of revolutions	≤65536 / 16 bit (adjustable)
Total resolution	≤ 31 bit
Absolute accuracy	±0.01 ° (ST 18 bit / MT 13 bit) ±0.025 ° (ST 13 bit / MT 16 bit)
Sensing method	Optical
Interference immunity	EN 61000-6-2
Emitted interference	EN 61000-6-4
Status indicator	4x LED integrated in housing
Approval	UL approval / E63076

#### Technical data - mechanical design

Size (flange)	ø58 mm
Shaft type	ø6 x 10 mm, solid shaft with flat
Flange	Synchro flange
Protection EN 60529	IP 54 IP 65 IP 67

#### Technical data - mechanical design

Operating speed	≤10000 rpm (mechanical) ≤6000 rpm (electric)
Starting acceleration	≤1000 U/s <sup>2</sup>
Starting torque	≤0.03 Nm (+25 °C, IP 65/IP 67) ≤0.015 Nm (+25 °C, IP 54)
Rotor moment of inertia	20 gcm <sup>2</sup>
Admitted shaft load	≤20 N axial ≤40 N radial
Material	Housing: zinc diecast Flange: aluminium
Operating temperature	-40...+85 °C (see general information)
Relative humidity	95 % non-condensing
Resistance	EN 60068-2-6 Vibration ±0.75 mm - 10-58 Hz 10 g - 58-2000 Hz EN 60068-2-27 Shock 100 g, 2 ms
Weight approx.	500 g
Connection	Flange connector 3 x M12

### Optional

- Button for Preset

## EAL580-SV - EtherCAT

Solid shaft with synchro flange

Optical multiturn encoders 18 bit ST / 16 bit MT, EtherCAT


### General information

Self-heating interrelated to speed, protection, attachment method and ambient conditions as well electronics and supply voltage must be considered for precise thermal dimensioning. Self-heating is supposed to approximate 4 K (IP 54 protection) respectively 6 K (IP 65 / IP 67 protection) per 1000 rpm. Operating the encoder close to the maximum limits requires measuring the real prevailing temperature at the encoder flange.

### Terminal assignment

#### Voltage supply

Pin	Assigned	Significance
1	UB	Voltage supply
2	d.u.	Do not connect
3	GND	Ground
4	d.u.	Do not connect




1 x flange connector M12 (male), A-coded

#### EtherCAT (data line)

Pin	Assigned	Significance
1	TxD+	Transmission data+
2	RxD+	Receiving data+
3	TxD-	Transmission data-
4	RxD-	Receiving data-



2 x flange connector M12 (female), D-coded



### EtherCAT features


Bus protocol	EtherCAT
Device profile	Encoder-Profil CANopen® CiA 406 Vers. 4.0.2 from 18.08.2016
Operating modes	Free Run, Synchronous with SM3 Event, DC Mode (Distributed Clocks)
Cycle time	Min. 62.5 µs
Features	<ul style="list-style-type: none"> <li>- Gear factor (round shaft) and endless loop mode</li> <li>- Time stamp (time of position data acquisition)</li> <li>- Plausibility check of the configurable parameters</li> <li>- Comprehensive diagnostic functions</li> <li>- Preset button for position</li> <li>- File Access over EtherCAT (FoE)</li> </ul>
Process data	<ul style="list-style-type: none"> <li>- Position value 32 bits input data with/without speed 32 bits</li> <li>- Extensive process data mapping</li> </ul>
LED status indicator	2x Link/Activity, RUN, ERR

## EAL580-SV - EtherCAT

Solid shaft with synchro flange

Optical multiturn encoders 18 bit ST / 16 bit MT, EtherCAT

## Dimensions



## EAL580-SV - EtherCAT

Solid shaft with synchro flange

Optical multiturn encoders 18 bit ST / 16 bit MT, EtherCAT

### Ordering reference

	EAL580	-	S	V	6	.	#	W	EC	.	##	##	0	.	A
<b>Product</b>	EAL580														
<b>Shaft type</b>															
Solid shaft				S											
<b>Flange (shaft)</b>															
Synchro flange, ø52 mm, M4				V											
<b>Shaft</b>															
ø6 x 10 mm, with flat					6										
<b>Protection class</b>															
IP 54								4							
IP 65								5							
IP 67								7							
<b>Connection</b>															
Flange socket radial, 2 x M12, 4-pin, female contacts, D-coded, 1 x M12, 4-pin, male contacts, A-coded								W							
<b>Voltage supply / interface</b>															
10...30 VDC, EtherCAT									EC						
<b>Resolution Singleturn</b>															
13 Bit												13			
18 Bit												18			
<b>Resolution Multiturn</b>															
13 Bit													13		
16 Bit													16		
<b>Resolution supplement</b>															
No option														0	
<b>Operating temperature</b>															A
-40...+85 °C															

### Accessories

#### Mounting accessories

10117669	Eccentric fixing, single (Z 119.006)
10117667	Mounting adaptor for encoders with synchro flange (Z 119.015)
10158124	Bearing flange for encoders with synchro flange (Z 119.035)
11177167	Self-tapping grounding screw (Z 119.100)
10141132	Spring washer coupling D1=6 / D2=10 (Z 121.C01)
10141131	Spring washer coupling D1=6 / D2=6 (Z 121.C02)
11034143	Slit coupling D1=06 / D2=06 (Z 121.D01)