

## Overview

- 150 mm
- 800 mm
- pulsed infrared diode
- PNP
- Teach-in
- cable 4 pin, 2 m
- -25 ... 55 °C
- IP 67



Picture similar



## Technical data

### General data

Actual range Sb	800 mm
Sensing distance Tw	150 mm
Light source	Pulsed infrared diode
Light indicator	LED green
Alignment / soiled lens indicator	LED green, flashing
Output indicator	LED yellow
Adjustment	Teach-in
Wave length	880 nm
Suppression of reciprocal influence	Yes

### Electrical data

Response time / release time	< 1 ms
Voltage supply range +Vs	10 ... 30 VDC
Current consumption max. (no load)	55 mA

### Electrical data

Current consumption typ.	40 mA
Voltage drop Vd	<1.8 VDC
Output function	Light / dark operate switchable
Output circuit	PNP
Output current	200 mA
Short circuit protection	Yes
Reverse polarity protection	Yes


### Mechanical data

Width / diameter	18 mm
Height / length	50 mm
Type	Cylindrical threaded
Housing material	Brass nickel plated / PC
Connection types	Cable 4 pin, 2 m

### Ambient conditions

Operating temperature	-25 ... +55 °C
Protection class	IP 67

**Dimension drawing**



**Connection diagram**

