

## HXC40

Camera Link®, 4 Megapixel, Monochrome

Article number: 11047481

### Overview

- 2048 × 2048 px
- ams (CMOSIS) CMV4000
- 1" CMOS
- 180 fps
- Camera Link® Full



### Technical data

#### Sensor information

Sensor	ams (CMOSIS) CMV4000
Mono/Color	Mono
Sensor type	1" CMOS
Shutter type	Global shutter
Resolution	2048 × 2048 px
Pixel size	5.5 × 5.5 µm
Exposure time	0.02 ... 1000 ms

#### Acquisition formats

Image formats, interface frame rate max.	Full Frame, 2048 × 2048 px, max. 180 fps Binning 2×1, 1024 × 2048 px, max. 180 fps Subsampling 2×2, 1024 × 1024 px, max. 357 fps
Pixel formats	Mono8 Mono10 Mono12

#### Image preprocessing

Analog controls	Gain (0 ... 12 dB) Offset (0 ... 255 LSB)
Color models	Mono

#### Camera features

Synchronization	free running trigger
Trigger sources	Hardware Software FrameGrabber
Trigger delay	0 ... 2 sec, tracking and buffering of up to 512 trigger signals

#### Camera features

Sequencer	Automated control for series of images using different sets of parameters
Sequencer parameter	Exposure time gain factor Output
Digital inputs	3 input line (each with Debouncer)
Digital outputs	3 output lines
Internal image buffer	256 MB

#### Interfaces and connectors

Data interface	Camera Link Full, connector: 2 x Standard SDR26 (Mini CL)
Process interface	M8 / 8 pins
Power supply	via M8 / 3 pins

#### Mechanical data

Lens mount	C-mount (F-mount on request)
Width	52 mm
Height	52 mm
Depth	37 mm
Weight	≤ 185 g
Material	housing: aluminum

#### Electrical data

Voltage supply range +Vs	9.6 ... 30 V DC
Power consumption	approx. 5.5 W

#### Environmental conditions

Operating temperature	+5 ... +60 °C
Humidity	10 ... 90 % (non-condensing)

## HXC40

Camera Link®, 4 Megapixel, Monochrome

Article number: 11047481

### Technical data

#### Environmental conditions

Protection class IP 40

#### Conformity

Conformity CE  
RoHS  
FCC  
KC (MISP-REI-BkR-HXC40)  
EAC

### Dimension drawing

