

IFRM 06P1707

Inductive sensors special versions - high temperature

Article number: 10229690

Overview

- 2 mm
- PNP make function (NO)
- cable FEP, 1 m
- -25 ... 100 °C
- IP 67



Picture similar



Technical data

General data

Mounting type	Flush
Special type	High temperature
Nominal sensing distance S _n	2 mm
Temperature drift	± 10 % (-25 ... +75 °C) - 10 % / + 15 % (-25 ... +100 °C)
Hysteresis	3 ... 20 % of S _r

Electrical data

Switching frequency	5 kHz
Voltage supply range +V _s	6 ... 30 VDC
Current consumption max. (no load)	12 mA
Output circuit	PNP make function (NO)
Voltage drop V _d	< 2 VDC

Electrical data

Output current	< 100 mA
Short circuit protection	Yes
Reverse polarity protection	Yes

Mechanical data

Type	Cylindrical smooth
Material (sensing face)	PBT
Housing material	Stainless steel
Dimension	6.5 mm
Housing length	30 mm
Connection types	Cable FEP, 1 m

Ambient conditions

Operating temperature	-25 ... +100 °C
Protection class	IP 67

Remarks


- With integral electronics of up to +100 °C

IFRM 06P1707

Inductive sensors special versions - high temperature

Article number: 10229690

Dimension drawing



Connection diagram

